

E06a: UC^{FIBRE} O CT CST PE 3.0KN

3000N, CT up to 24 fibres, glass yarns, steel tape armour, PE sheath



GENERAL INFO

Fibre optic cable with central loose tube filled with gel and up to 24 fibres for outdoor applications and direct burial installations. Metallic armoured design with glass yarns, longitudinally water blocked, rodent-proof and PE sheath. Used for LAN and WAN backbones, telecom access lines, fibre to business and fibre to the building drop connections as well as fibre to the home drop and access connections. DIN/VDE: A-D(ZN)(SR)B2Y

More information on fiber optic cable applications: [read more](#)

Latest version of this data sheet is available for download: [ProductFamily238991](#)

CERTIFICATIONS AND DESIGN STANDARDS

ISO/IEC 11801

EN 50173

IEC 60794-1-1

IEC 60794-1-21

IEC 60794-1-22

Generic telecom cabling for customer premises
Information technology - Generic cabling systems
Generic Specification Fibre Optic Cables
Mechanical Test Methods
Environmental Test Procedures

APPLICATION PROPERTIES

Resistant to UV	Good
Outdoor installation With rodent protection	Yes
Operation temperature (min) [°C]	-40 and (max) [°C] 70
Installation temperature (min) [°C]	-15 and (max) [°C] 60
Storage temperature (min) [°C]	-40 and (max) [°C] 70
Bending radius (rule)	During installation (loaded) = 20xOD, Permanent (unloaded) = 10xOD

CABLE CONSTRUCTION

Type of tube	Central tube cable with Ø2.8 mm gel-filled loose tube up to 24fo
Longitudinal water blocking cable	Yes*
Armouring/reinforcement	Corrugated Steel, galvanised tape + glass Yarns
Material outer sheath	1.5mm, MDPE,
Cable shape	Round
Cable marking example	PRYSMIAN UC FIBRE O CT CST PE 3.0 kN 'Fibre count' 'Fibre type' 'Fibre brand' 'Item No' 'factory code' 'Batch Number' 'Meter mark' 'A-D(ZN)(SR)2Y' 'Fibre count' 'Fibre family' 'Mode field diameter' '125' 'Transmission Class'

* Longitudinal water blocking test method according to IEC 60794-1-22 F5B and limited to the gell filled cable core.

IDENTIFICATION

Fibre colour code	1 Red	13 Red w/mark every 70mm
<i>in accordance with IEC 60794-2 and VDE 0888 read more</i>	2 Green	14 Green w/mark every 70mm
	3 Blue	15 Blue w/mark every 70mm
	4 Yellow	16 Yellow w/mark every 70mm
	5 White	17 White w/mark every 70mm
	6 Grey	18 Grey w/mark every 70mm
	7 Brown	19 Brown w/mark every 70mm
	8 Violet	20 Violet w/mark every 70mm
	9 Turquoise	21 Turquoise w/mark every 70mm
	10 Black	22 White w/mark every 35mm
	11 Orange	23 Orange w/mark every 70mm
	12 Pink	24 Pink w/mark every 70mm
Colour outer sheath	Black, RAL 9005	

MECHANICAL PROPERTIES

Nominal outer diameter		8.5 mm
Cable weight		83 kg/km
Crush test (short term)	IEC 60794-1-21 E3	2,200 N/10cm
Crush test (long term)	IEC 60794-1-21 E3	1,100 N/10cm
Torsion test *	IEC 60794-1-21 E7	5 cycles ±1turn
Impact test	IEC 60794-1-21 E4	30 N·m
Max. tensile strength during installation	IEC 60794-1-21 E1	3,000 N
Permanent tensile strength		1,000 N
Kink test	IEC 60794-1-21 E10	The cables do not form a kink when a loop is drawn together to a diameter 20 times the cable nominal diameter.
Bending		Installation: 170 mm / Operation: 85 m
Water penetration	IEC 60794-1-22	No water on free end

CABLE DETAILS

Product name	Number of fibres	Category (fibre)	Fibre datasheet	SAP code
UCFIBRE O CT CST PE 3kN 4 SM7A1 BK	4	OS2	C17	60018850
UCFIBRE O CT CST PE 3kN 6 SM7A1 BK	6	OS2	C17	60018744
UCFIBRE O CT CST PE 3kN 8 SM7A1 BK	8	OS2	C17	60018747
UCFIBRE O CT CST PE 3kN 12 SM7A1 BK	12	OS2	C17	60018750
UCFIBRE O CT CST PE 3kN 16 SM7A1 BK	16	OS2	C17	60011340
UCFIBRE O CT CST PE 3kN 24 SM2D/SM7A1 BK	24	OS2	C17	60071175
UCFIBRE O CT CST PE 3kN 4 OM2B BK	4	OM2	C34	60011387
UCFIBRE O CT CST PE 3kN 6 OM2B BK	6	OM2	C34	60018892
UCFIBRE O CT CST PE 3kN 8 OM2B BK	8	OM2	C34	60018893
UCFIBRE O CT CST PE 3kN 12 OM2B BK	12	OM2	C34	60018894
UCFIBRE O CT CST PE 3kN 24 OM2B BK	24	OM2	C34	60069233
UCFIBRE O CT CST PE 3kN 4 OM3B BK	4	OM3	C31	60018856
UCFIBRE O CT CST PE 3kN 6 OM3B BK	6	OM3	C31	60019590
UCFIBRE O CT CST PE 3kN 8 OM3B BK	8	OM3	C31	60019384
UCFIBRE O CT CST PE 3kN 12 OM3B BK	12	OM3	C31	60011435
UCFIBRE O CT CST PE 3kN 24 OM3B BK	24	OM3	C31	60069232
UCFIBRE O CT CST PE 3kN 4 OM4B BK	4	OM4	C32	60065311
UCFIBRE O CT CST PE 3kN 6 OM4B BK	6	OM4	C32	60055105
UCFIBRE O CT CST PE 3kN 8 OM4B BK	8	OM4	C32	60043719
UCFIBRE O CT CST PE 3kN 12 OM4B BK	12	OM4	C32	60019807
UCFIBRE O CT CST PE 3kN 24 OM4B BK	24	OM4	C32	60071180
UCFIBRE O CT CST PE 3kN 4 MM61 BK	4	OM1	C02	60018741
UCFIBRE O CT CST PE 3kN 6 MM61 BK	6	OM1	C02	60018743
UCFIBRE O CT CST PE 3kN 8 MM61 BK	8	OM1	C02	60018746
UCFIBRE O CT CST PE 3kN 12 MM61 BK	12	OM1	C02	60018749
UCFIBRE O CT CST PE 3kN 16 MM61 BK	16	OM1	C02	60011298
UCFIBRE O CT CST PE 3kN 24 MM61 BK	24	OM1	C02	60069234
UCFIBRE O CT CST PE 3kN 24 SM/MM BK	24	OS2+OM1	C02,C17	60071724

©PRYSMIAN 2025, all rights reserved. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by Prysmian.