

E19: UC^{FIBRE} I/O CT CST LSHF-FR B2_{ca} 3.0KN

3000N, CT up to 24 fibres, glass yarns, steel tape, FireRes® sheath



**B2_{ca}
CPR**

GENERAL INFO

Fibre optic cable with central loose tube filled with gel for structured cabling. Water-blocked central tube cable up to 24 fibres with glass yarns and corrugated steel tape armour for rodent protection. Use outdoors for duct installation and with its FireRes® sheathing this cable is very a high flame retardant solution ideal for indoor installations and buildings with high personal risk. It can be used for LAN, fibre to business, fibre to the building drop connections as well as fibre to the home drop and access connections. Short outdoor applications. DIN/VDE: U-D(ZN)(SR)H

Latest version of this data sheet is available for download: [ProductFamily239108](#)

CERTIFICATIONS AND DESIGN STANDARDS



ISO/IEC 11801
EN 50173
EN 50575
IEC 60794-1-1
IEC 60794-1-21
IEC 60794-1-22
IEC 60794-6-10

Generic telecom cabling for customer premises
Information technology - Generic cabling systems
Cables in construction works subject to reaction to fire
Generic Specification Fibre Optic Cables
Mechanical Test Methods
Environmental Test Procedures
Family specification for universal indoor-outdoor cables

APPLICATION PROPERTIES

Resistant to UV
Outdoor installation With rodent protection
Operation temperature (min) [°C]
Installation temperature (min) [°C]
Storage temperature (min) [°C]
Bending radius (rule)

UV stabilised
Yes
-40 and (max) [°C] 70
-20 and (max) [°C] 60
-30 and (max) [°C] 60
During installation (loaded) = 20xOD, Permanent (unloaded) = 10xOD

CABLE CONSTRUCTION

Type of tube	Central tube cable with Ø2.8 mm gel-filled loose tube up to 24fo
Longitudinal water blocking cable	Yes*
Armouring/reinforcement	Corrugated Steel, galvanised tape + glass Yarns
Material outer sheath	1.5mm, Low smoke zero halogen, FireRes®
Cable shape	Round
Cable marking example	PRYSMIAN UCFIBRE I/O CT CST LSHF-FR B2ca-s1a-d1-a1 3.0 kN 'Fibre count ' 'Fibre type ' 'Fibre brand ' 'Item No ' 'Factory Code ' 'Batch Number ' 'Meter mark ' U-D(ZN) (SR)H 'Fibre count ' 'Fibre family ' 'Mode field diameter ' /125 'Transmission Class '

* Longitudinal water blocking test method according to IEC 60794-1-22 F5B and limited to the gell filled cable core.

IDENTIFICATION

Fibre colour code	1 Red	13 Red w/mark every 70mm
<i>in accordance with IEC 60794-2 and VDE 0888 read more</i>	2 Green	14 Green w/mark every 70mm
	3 Blue	15 Blue w/mark every 70mm
	4 Yellow	16 Yellow w/mark every 70mm
	5 White	17 White w/mark every 70mm
	6 Grey	18 Grey w/mark every 70mm
	7 Brown	19 Brown w/mark every 70mm
	8 Violet	20 Violet w/mark every 70mm
	9 Turquoise	21 Turquoise w/mark every 70mm
	10 Black	22 White w/mark every 35mm
	11 Orange	23 Orange w/mark every 70mm
	12 Pink	24 Pink w/mark every 70mm

Sheath color	Cable with SM fibres: BendBrightXSG.657.A2, BendBright G.657.A1 Yellow, RAL 1018 Cable with mixed fibre types (hybrid) Blue, RAL 5015 Cable with OM1 Grey, RAL 7037 Cable with MaxCap-BendBright-OM2 Orange, RAL 2009 Cable with MaxCap-BendBright-OM3 Aqua, RAL 6027 Cable with MaxCap-BendBright-OM4 Erika-Violet, RAL 4003 Cable with BendBright WideCap-OM5 Lime-Green, RAL 6039
--------------	--

MECHANICAL PROPERTIES

Nominal outer diameter		8,5 mm
Cable weight		100 kg/km
Fire load		1,186 MJ/km
Crush test	IEC 60794-1-21 E3	2,200 N/10cm
Torsion test	IEC 60794-1-21 E7	5 cycles ±1turn
Impact test	IEC 60794-1-21 E4	30 N·m
Max. tensile strength during installation	IEC 60794-1-21 E1	3,000 N
Permanent tensile strength	IEC 60794-1-21 E1	1,000 N
Kink test	IEC 60794-1-21 E10	The cables do not form a kink when a loop is drawn together to a diameter 20 times the cable nominal diameter.

FIRE PROPERTIES

Flame retardant	acc. IEC/EN 60332-1-2, EN 50399
Halogen free	acc. IEC/EN 60754-2
Low smoke	acc. IEC/EN 61034-2
The reaction to fire according to the EN 50575	B2ca - s1a, d1, a1

ORDERING DETAILS

Product name	Number of fibres	Category (fibre)	Fibre datasheet	DOP number	SAP code
UCFIBRE I/O CT CST LSHF-FR B2 4 SM7A1 YL	4	OS2	C17	1012732	60071614
UCFIBRE I/O CT CST LSHF-FR B2 6 SM7A1 YL	6	OS2	C17	1012733	60071615
UCFIBRE I/O CT CST LSHF-FR B2 8 SM7A1 YL	8	OS2	C17	1012534	60071735
UCFIBRE I/O CT CST LSHF-FR B2 12 SM7A1 YL	12	OS2	C17	1012573	60084725
UCFIBRE I/O CT CST LSHF-FR B2 24 SM7A1 YL	24	OS2	C17	1012710	60067059
UCFIBRE I/O CT CST LSHF-FR B2 2 OM2B OR	2	OM2	C34	1012847	60085119
UCFIBRE I/O CT CST LSHF-FR B2 4 OM2B OR	4	OM2	C34	1012785	60077130
UCFIBRE I/O CT CST LSHF-FR B2 12 OM2B OR	12	OM2	C34	1012744	60071903
UCFIBRE I/O CT CST LSHF-FR B2 24 OM2B OR	24	OM2	C34	1012745	60071904
UCFIBRE I/O CT CST LSHF-FR B2 4 OM3 AQ	4	OM3	C31	1012795	60079544
UCFIBRE I/O CT CST LSHF-FR B2 8 OM3B AQ	8	OM3	C31	1012758	60072991
UCFIBRE I/O CT CST LSHF-FR B2 12 OM3B AQ	12	OM3	C31	1012735	60071617
UCFIBRE I/O CT CST LSHF-FR B2 24 OM3B AQ	24	OM3	C31	1012746	60071906
UCFIBRE I/O CT CST LSHF-FR B2 4 OM4B EV	4	OM4	C32	1014631	60095045
UCFIBRE I/O CT CST LSHF-FR B2 6 OM4B EV	6	OM4	C32		60114785
UCFIBRE I/O CT CST LSHF-FR B2 8 OM4B EV	8	OM4	C32	1012602	60072992
UCFIBRE I/O CT CST LSHF-FR B2 12 OM4B EV	12	OM4	C32	1012514	60071907
UCFIBRE I/O CT CST LSHF-FR B2 24 OM4B EV	24	OM4	C32	1012572	60071620
UCFIBRE I/O CT CST LSHF-FR B2 12 OM5	12	OM5	C39	-	E19-12OEM5
UCFIBRE I/O CT CST LSHF-FR B2 24 OM5B LI	24	OM5	C39	1019264	60113571
UCFIBRE I/O CT CST LSHF-FR B2 4 MM61 SL	4	OM1	C02	1012562	60091912
UCFIBRE I/O CT CST LSHF-FR B2 6 MM61 SL	6	OM1	C02	1012622	60071833
UCFIBRE I/O CT CST LSHF-FR B2 8 MM61 SL	8	OM1	C02	1012843	60084171
UCFIBRE I/O CT CST LSHF-FR B2 12 MM61 SL	12	OM1	C02	1012763	60075296
UCFIBRE I/O CT CST LSHF-FR B2 24 MM61 SL	24	OM1	C02	1012844	60084240

© PRYSMIAN 2025, all rights reserved. All sizes and values without tolerances are reference values. Specifications are for product as supplied by PRYSMIAN: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PRYSMIAN. The information is believed to be correct at the time of issue. PRYSMIAN reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by PRYSMIAN.