

MCCMK-HF C-PRo 1 kV

Low smoke halogen-free EMC-screen-protected 1 kV power cable



GENERAL INFO

APPLICATION

EMC-protected cable for fixed installation indoors, outdoors and underground; as well as in building structures e.g. directly in concrete (but not in sliding joints). Also for circumstances where it is required to have installation cables with a low emission of smoke and corrosive gases in case of fire.

RATED VOLTAGE

$U_0/U = 0,6/1$ kV, $U_m = 1,2$ kV

Declaration of Performance (DoP)

Ref. no 1003352

STANDARDS AND CERTIFICATIONS



SFS 5546

IEC 60502-1

EN 50575:2014+A1:2016

EN 13501-6, class Cca-s1,d1,a1

IEC 60332-1-2

IEC 60332-3

IEC 61034

IEC 60754

1 kV & 3 kV power cables with extruded insulation.

hEN CPR cables

CPR fire class, Cca-s1,d1,a1

Vertical flame propagation for a single insulated wire or cable

Smoke density

Corrosive gases

Conductor

Copper

Conductor surface

Bare

Insulation

XLPE

Core identification (acc. HD 308 S2)

Yes

Screen construction

Metallised foil

Screen material

Copper, bare

Concentric conductor

Copper

Filling sheath

Halogenfree polymer

Outer sheath

Halogenfree polymer

APPLICATION PROPERTIES

Max. conductor temperature [°C]

90

Max. conductor temperature at short circuit [°C]

250

Permitted cable outer temperature during assembling/handling (min) [°C]

-15

Minimum permissible bending radius during laying

12x OD

© Prysmian Finland Oy. All rights reserved.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without notice.

This specification is not contractually valid unless specifically authorised by Prysmian.

FIRE PROPERTIES

Reaction-to-fire, CPR classification
Flame retardant
Halogen free
Low smoke

Cca-s1,d1,a1
In accordance with EN 13501-6
Yes
Yes

DELIVERY INFO

Snro	PRODUCT NAME	EAN-code (GTIN)	Packaging type	Standard delivery length
0602090	MCCMK-HF C-PRo 3x1,5/1,5 K8/1000 EMC	6410006020904	Drum	1,000
0601994	MCCMK-HF C-PRo 3x1,5/1,5 S4/150 EMC	6410006019946	Bobbin	150
0601997	MCCMK-HF C-PRo 3x2,5/2,5 K9/1000 EMC	6410006019977	Drum	1,000
0601998	MCCMK-HF C-PRo 3x2,5/2,5 S4/100 EMC	6410006019984	Bobbin	100
0601999	MCCMK-HF C-PRo 3x6/6 K11/1000 EMC	6410006019991	Drum	1,000
0601995	MCCMK-HF C-PRo 3x10/10 RM K12/1000 EMC	6410006019953	Drum	1,000
0601996	MCCMK-HF C-PRo 3x16/16 RM K14/1000 EMC	6410006019960	Drum	1,000
0602004	MCCMK-HF C-PRo 4x1,5/1,5 K8/1000 EMC	6410006020041	Drum	1,000
0602008	MCCMK-HF C-PRo 4x2,5/2,5 K9/1000 EMC	6410006020089	Drum	1,000
0602009	MCCMK-HF C-PRo 4x6/6 K9/500 EMC	6410006020096	Drum	500
0602005	MCCMK-HF C-PRo 4x10/10 RM K11/500 EMC	6410006020058	Drum	500
0602006	MCCMK-HF C-PRo 4x16/16 RM K11/500 EMC	6410006020065	Drum	500

© Prysmian Finland Oy. All rights reserved.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without notice.

This specification is not contractually valid unless specifically authorised by Prysmian.

MECHANICAL DATA

Product description (short)	Diameter over cable [mm]	Pulling force pulling head [N]	Pulling force with pulling hose [N]	Weight [kg/km]	Min. permissible bending radius during laying [mm]
MCCMK-HF C-PRo 3x1,5/1,5	12	200		200	150
MCCMK-HF C-PRo 3x2,5/2,5	13	300		250	160
MCCMK-HF C-PRo 3x6/6	16	900		420	200
MCCMK-HF C-PRo 3x10/10	19	1,500		670	230
MCCMK-HF C-PRo 3x16/16	22	2,400		950	270
MCCMK-HF C-PRo 4x1,5/1,5	13	300		230	160
MCCMK-HF C-PRo 4x2,5/2,5	14	500		290	170
MCCMK-HF C-PRo 4x6/6	17	1,200		500	210
MCCMK-HF C-PRo 4x10/10	21	2,000		800	260
MCCMK-HF C-PRo 4x16/16	23	3,200		1,100	280

© Prysmian Finland Oy. All rights reserved.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without notice.

This specification is not contractually valid unless specifically authorised by Prysmian.

ELECTRICAL DATA

Product description (short)	Nominal operation capacitance [nF/km]	Max. DC resistance, conductor (20°C) [ohm/km]	Operation self inductance [mH/km]	Screen DC resistance [Ohm/km]
MCCMK-HF C-PRo 3x1,5/1,5	0.25	12.1	0.34	12.1
MCCMK-HF C-PRo 3x2,5/2,5	0.25	7.41	0.32	7.41
MCCMK-HF C-PRo 3x6/6	0.26	3.08	0.3	3.08
MCCMK-HF C-PRo 3x10/10	0.27	1.83	0.29	1.83
MCCMK-HF C-PRo 3x16/16	0.28	1.15	0.28	1.15
MCCMK-HF C-PRo 4x1,5/1,5	0.25	12.1	0.34	12.1
MCCMK-HF C-PRo 4x2,5/2,5	0.25	7.41	0.32	7.41
MCCMK-HF C-PRo 4x6/6	0.26	3.08	0.3	3.08
MCCMK-HF C-PRo 4x10/10	0.27	1.83	0.29	1.83
MCCMK-HF C-PRo 4x16/16	0.28	1.15	0.28	1.15

© Prysmian Finland Oy. All rights reserved.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without notice.

This specification is not contractually valid unless specifically authorised by Prysmian.

CURRENT DATA

Product description (short)	Short circuit current conductor (1sec) [kA]	Short circuit current screen (1sec) [kA]	Current rating, ref. install. type E [A]	Current rating, ref. install. type D [A]
MCCMK-HF C-PRo 3x1,5/1,5	0.2	0.2	24	26
MCCMK-HF C-PRo 3x2,5/2,5	0.4	0.4	33	35
MCCMK-HF C-PRo 3x6/6	0.9	0.9	56	57
MCCMK-HF C-PRo 3x10/10	1.4	1.5	78	77
MCCMK-HF C-PRo 3x16/16	2.2	2.4	104	100
MCCMK-HF C-PRo 4x1,5/1,5	0.2	0.2	24	26
MCCMK-HF C-PRo 4x2,5/2,5	0.4	0.4	33	35
MCCMK-HF C-PRo 4x6/6	0.9	0.9	56	57
MCCMK-HF C-PRo 4x10/10	1.4	1.5	78	77
MCCMK-HF C-PRo 4x16/16	2.2	2.4	104	100

Current load, installation method E (in free air), conductor max.operation temp. Installation method D2 (in ground), conductor +65 °C

© Prysmian Finland Oy. All rights reserved.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without notice.

This specification is not contractually valid unless specifically authorised by Prysmian.